



# 3214

## INTERRUPT CONTROL UNIT

The Intel®3214 Interrupt Control Unit (ICU) implements multi-level interrupt capability for systems designed with Series 3000 computing elements.

The ICU accepts an asynchronous interrupt strobe from the 3001 Microprogram Control Unit or a bit in microprogram memory and generates a synchronous interrupt acknowledge and an interrupt vector which may be directed to the MCU or CP Array to uniquely identify the interrupt source.

The ICU is fully expandable in 8-level increments and provides the following system capabilities:

- Eight unique priority levels per ICU
- Automatic Priority Determination
- Programmable Status
- N-level expansion capability
- Automatic interrupt vector generation

High Performance – 80 ns Cycle Time

Compatible with Intel 3001 MCU and 3002 CPE

8-Bit Priority Interrupt Request Latch

4-Bit Priority Status Latch

3-Bit Priority Encoder with Open Collector Outputs



DTL and TTL Compatible

8-Level Priority Comparatör

Fully Expandable

24-Pin DIP

### PACKAGE CONFIGURATION



## PIN DESCRIPTION

PIN	SYMBOL	NAME AND FUNCTION	TYPE <sup>(1)</sup>
1–3	B <sub>0</sub> –B <sub>2</sub>	Current Status Inputs The Current Status inputs carry the binary value modulo 8 of the current priority level to the current status latch.	Active LOW
4	SGS	Status Group Select Input The Status Group Select input informs the ICU that the current priority level does belong to the group level assigned to the ICU.	Active LOW
5	IA	Interrupt Acknowledge The Interrupt Acknowledge Output will only be active from the ICU (multi-ICU system) which has received a priority request at a level superior to the current status. It signals the controlled device (usually the processor) and the other ICUs OR-tied on the Interrupt Acknowledge line that an interrupt request has been recognized. The IA signal also sets the Interrupt Disable flip-flop (it overrides the clear function of the ECS input).	Active LOW Open-Collector Output
6	CLK	Clock Input The Clock input is used to synchronize the interrupt acknowledge with the operation of the device which it controls.	
7	ISE	Interrupt Strobe Enable Input The Interrupt Strobe Enable input informs the ICU that it is authorized to enter the interrupt mode.	
8–10	A <sub>0</sub> –A <sub>2</sub>	Request Level Outputs When valid, the Request Level outputs carry the binary value (modulo 8) of the highest priority request present at the priority request inputs or stored in the priority request latch. The request level outputs can become active only with the ICU which has received the highest priority request with a level superior to the current status.	Active LOW Open-Collector
11	ELR	Enable Level Read Input When active, the Enable Level Read input enables the Request Level output buffers (A <sub>0</sub> –A <sub>2</sub> ).	Active LOW
12	GND	Ground	
13	ETLG	Enable This Level Group Input The Enable This Level Group input allows a higher priority ICU in multi-ICU systems to inhibit interrupts within the next lower priority ICU (and all the following ICUs).	
14	ENLG	Enable Next Level Group Output The Enable Next Level Group output allows the ICU to inhibit interrupts within the lower priority ICU in a multi-ICU system.	
15–22	R <sub>0</sub> –R <sub>7</sub>	Priority Interrupt Request Inputs The Priority Interrupt Request inputs are the inputs of the priority Interrupt Request Latch. The lowest priority level interrupt request signal is attached to R <sub>0</sub> and the highest is attached to R <sub>7</sub> .	Active LOW
23	ECS	Enable Current Status Input The Enable Current Status input controls the current status latch and the clear function of the Interrupt Inhibit flip-flop.	Active LOW
24	V <sub>CC</sub>	+5 Volt Supply	

## NOTE:

(1) Active HIGH, unless otherwise noted.

## FUNCTIONAL AND LOGICAL DESCRIPTION

The ICU adds interrupt capability to suitably microprogrammed processors or controllers. One or more of these units allows external signals called interrupt requests to cause the processor/controller to suspend execution of the active process, save its status, and initiate execution of a new task as requested by the interrupt signal.

It is customary to strobe the ICU at the end of each instruction execution. At that time, if an interrupt request is acknowledged by the ICU, the MCU is forced to follow the interrupt microprogram sequence.

Figure 1 shows the block diagram of the ICU. Interrupt requests pass through the interrupt request latch and priority encoder to the magnitude comparator. The output of the priority encoder is the binary equivalent of the highest active priority request. At the comparator, this value is compared with the Current Status (currently active priority level) contained in the current status latch. A request, if acknowledged at interrupt strobe time, will cause the interrupt flip-flop to enter the "interrupt active" state for one microinstruction cycle. This action causes the interrupt acknowledge (IA) signal to go low and sets the interrupt disable flip-flop.

The IA signal constitutes the interrupt command to the processor. It can directly force entry into the interrupt service routine as demonstrated in the appendix. As part of this routine, the microprogram normally reads the requesting level via the request level output bus. This information which is saved in the request latch can be enabled onto one of the processor input data buses using the enable level read input. Once the interrupt handler has determined the requesting level, it normally writes this level back into the current status register of the ICU. This action resets the interrupt disable flip-flop and acts to block any further request at this level or lower levels.

Entry into a macro level interrupt service routine may be vectored using the request level information to generate a subroutine address which corresponds to the level. Exit from such a macroprogram should normally restore the prior status in the current status latch.

The Enable This Level Group (ETLG) input and the Enable Next Level Group (ENLG) output can be used in a daisy chain fashion, as each ICU is capable of inhibiting interrupts from all of the following ICUs in a multiple ICU configuration.

The interrupt acknowledge flip-flop is set to the active LOW state on the rising edge of the clock when the following conditions are met:

- An active request level ( $R_0-R_7$ ) is greater than the current status  $B_0-B_2$

- The interrupt mode (ISE) is active
- ETLG is enabled

- The interrupt disable flip-flop is reset

When active, the IA signal asynchronously sets the disable flip-flop and holds the requests in the request latch until new current status information ( $B_0-B_2$ , SGS) is enabled (ECS) into the current status latch. The disable flip-flop is reset at the completion of this load operation.

During this process, ENLG will be enabled only if the following conditions are met:

- ETLG is enabled

- The current status (SGS) does not belong to this level group

- There is no active request at this level

The request level outputs  $A_0-A_2$  and the IA output are open-collector to permit bussing of these lines in multi-ICU configuration.




Figure 1. 3214 Block Diagram.

**D.C. AND OPERATING CHARACTERISTICS****ABSOLUTE MAXIMUM RATINGS\***

## Temperature Under Bias

Ceramic . . . . . -65°C to +75°C

Plastic . . . . . 0°C to +75°C

Storage Temperature . . . . . -65°C to +160°C

All Output and Supply Voltages. . . . . -0.5V to +7V

All Input Voltages. . . . . -1.0V to +5.5V

Output Currents . . . . . 100 mA

*\*COMMENT:* Stresses above those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational section of this specification is not implied. Exposure to absolute maximum ratings for extended periods may affect device reliability.

$T_A = 0^\circ\text{C to } +75^\circ\text{C}, V_{CC} = 5.0\text{V } \pm 5\%$

SYMBOL	PARAMETER	LIMITS			UNIT	CONDITIONS
		MIN	TYP <sup>(1)</sup>	MAX		
$V_C$	Input Clamp Voltage (all inputs)			-1.0	V	$I_C = -5 \text{ mA}$
$I_F$	Input Forward Current:	ETLG input	-0.15	-0.5	mA	$V_F = 0.45\text{V}$
		all other inputs	-0.08	-0.25	mA	
$I_R$	Input Reverse Current:	ETLG input		80	$\mu\text{A}$	$V_R = 5.25\text{V}$
		all other inputs		40	$\mu\text{A}$	
$V_{IL}$	Input LOW Voltage:			0.8	V	$V_{CC} = 5.0\text{V}$
$V_{IH}$	Input HIGH Voltage:	2.0			V	$V_{CC} = 5.0\text{V}$
$I_{CC}$	Power Supply Current <sup>(2)</sup>		90	130	mA	
$V_{OL}$	Output LOW Voltage:		.3	.45	V	$I_{OL} = 15 \text{ mA}$
$V_{OH}$	Output HIGH Voltage:	2.4	3.0		V	$I_{OH} = -1 \text{ mA}$
$I_{OS}$	Short Circuit Output Current:	-20	-35	-55	mA	$V_{CC} = 5.0\text{V}$
$I_{CEX}$	Output Leakage Current:			100	$\mu\text{A}$	$V_{CEX} = 5.25\text{V}$
						IA and A <sub>0</sub> -A <sub>2</sub> outputs

## NOTES:

(1) Typical values are for  $T_A = 25^\circ\text{C}$  and nominal supply voltage.

(2) B<sub>0</sub>-B<sub>2</sub>, SGS, CLK, R<sub>0</sub>-R<sub>4</sub> grounded, all other inputs and all outputs open.

## A.C. CHARACTERISTICS

 $T_A = 0^\circ\text{C to } +75^\circ\text{C}, V_{CC} = +5\text{V} \pm 5\%$ 

SYMBOL	PARAMETER	MIN	LIMITS TYP(1)	MAX	UNIT
$t_{CY}$	CLK Cycle Time	80			ns
$t_{PW}$	CLK, ECS, IA Pulse Width	25	15		ns
<i>Interrupt Flip-Flop Next State Determination:</i>					
$t_{ISS}$	ISE Set-Up Time to CLK	16	12		ns
$t_{ISH}$	ISE Hold Time After CLK	20	10		ns
$t_{ETCS}^2$	ETLG Set-Up Time to CLK	25	12		ns
$t_{ETCH}^2$	ETLG Hold Time After CLK	20	10		ns
$t_{ECCS}^3$	ECS Set-Up Time to CLK (to clear interrupt inhibit prior to CLK)	80	25		ns
$t_{ECCH}^3$	ECS Hold Time After CLK (to hold interrupt inhibit)	0			ns
$t_{ECSR}^3$	ECS Set-Up Time to CLK (to enable new requests through the request latch)	110	70		ns
$t_{ECRH}^3$	ECS Hold Time After CLK (to hold requests in request latch)	0			ns
$t_{ECSS}^2$	ECS Set-Up Time to CLK (to enable new status through the status latch)	75	70		ns
$t_{ECSH}^2$	ECS Hold Time After CLK (to hold status in status latch)	0			ns
$t_{DCS}^2$	SGS and $B_0$ - $B_2$ Set-Up Time to CLK (current status latch enabled)	70	50		ns
$t_{DCH}^2$	SGS and $B_0$ - $B_2$ Hold Time After CLK (current status latch enabled)	0			ns
$t_{RCS}^3$	$R_0$ - $R_7$ Set-Up Time to CLK (request latch enabled)	90	55		ns
$t_{RCH}^3$	$R_0$ - $R_7$ Hold Time After CLK (request latch enabled)	0			ns
$t_{ICS}$	IA Set-Up Time to CLK (to set interrupt inhibit F.F. before CLK)	55	35		ns
$t_{CI}$	CLK to IA Propagation Delay		15	25	ns
<i>Contents of Request Latch and Request Level Output Status Determination:</i>					
$t_{RIS}^4$	$R_0$ - $R_7$ Set-Up Time to IA	10	0		ns
$t_{RIH}^4$	$R_0$ - $R_7$ Hold Time After IA	35	20		ns
$t_{RA}$	$R_0$ - $R_7$ to $A_0$ - $A_2$ Propagation Delay (request latch enabled)		80	100	ns
$t_{ELA}$	ELR to $A_0$ - $A_2$ Propagation Delay		40	55	ns
$t_{ECA}$	ECS to $A_0$ - $A_2$ Propagation Delay (to enable new requests through request latch)		100	120	ns
$t_{ETA}$	ETLG to $A_0$ - $A_2$ Propagation Delay		35	70	ns

## A.C. CHARACTERISTICS (CONT')


SYMBOL	PARAMETER	LIMITS			UNIT
		MIN	TYP <sup>(1)</sup>	MAX	
<i>Contents of Current Priority Status Latch Determination:</i>					
$t_{DECS}^4$	SGS and B <sub>0</sub> -B <sub>2</sub> Set-Up Time to ECS	15	10		ns
$t_{DECH}^4$	SGS and B <sub>0</sub> -B <sub>2</sub> Hold Time After ECS	15	10		ns
<i>Enable Next Level Group Determination:</i>					
$t_{REN}$	R <sub>0</sub> -R <sub>7</sub> to ENLG Propagation Delay		45	70	ns
$t_{ETEN}$	ETLG to ENLG Propagation Delay		20	25	ns
$t_{ECRN}$	ECS to ENLG Propagation Delay (enabling new request through the request latch)		85	90	ns
$t_{ECSN}$	ECS to ENLG Propagation Delay (enabling new SGS through status latch)		35	55	ns

## NOTES:

- (1) Typical values are for  $T_A = 25^\circ\text{C}$  and nominal supply voltage.  
 (2) Required for proper operation if ISE is enabled during next clock pulse.  
 (3) These times are not required for proper operation but for desired change in interrupt flip-flop.  
 (4) Required for new request or status to be properly loaded.  
 (5)  $t_{CY} = t_{ICS} + t_{CI}$

## TEST CONDITIONS:

Input pulse amplitude: 2.5 volts.  
 Input rise and fall times: 5 ns between 1 and 2 volts.  
 Output loading of 15 mA and 30 pf.  
 Speed measurements taken at the 1.5V levels.

CAPACITANCE<sup>(5)</sup>

$T_A = 25^\circ\text{C}$

SYMBOL	PARAMETER	LIMITS			UNIT
		MIN	TYP <sup>(1)</sup>	MAX	
$C_{IN}$	Input Capacitance		5	10	pf
$C_{OUT}$	Output Capacitance		7	12	pf

## TEST CONDITIONS:

$V_{BIAS} = 2.5\text{V}$ ,  $V_{CC} = 5\text{V}$ ,  $T_A = 25^\circ\text{C}$ ,  $f = 1\text{MHz}$

## NOTE:

- (5) This parameter is periodically sampled and not 100% tested.

## D.C. AND OPERATING CHARACTERISTICS

## ABSOLUTE MAXIMUM RATINGS\*

## Temperature Under Bias

CerDip . . . . .	-55°C to +125°C
Storage Temperature . . . . .	-65°C to +160°C
All Output and Supply Voltages . . . . .	-0.5V to +7V
All Input Voltages . . . . .	-1.0V to +5.5V
Output Currents . . . . .	100 mA

\*COMMENT: Stresses above those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational section of this specification is not implied. Exposure to absolute maximum ratings for extended periods may affect device reliability.

$T_A = -55^\circ\text{C}$  to  $+125^\circ\text{C}$ ;  $V_{CC} = 5.0\text{V} \pm 10\%$

SYMBOL	PARAMETER	MIN	LIMITS		UNIT	CONDITIONS	
			TYP(1)	MAX			
$V_C$	Input Clamp Voltage (all inputs)			-1.2	V	$I_C = -5\text{ mA}$	
$I_F$	Input Forward Current:		ETLG input	-.15	-0.5	mA	$V_F = 0.45\text{V}$
			all other inputs	-.08	-0.25	mA	
$I_R$	Input Reverse Current:		ETLG input		80	$\mu\text{A}$	$V_R = 5.5\text{V}$
			all other inputs		40	$\mu\text{A}$	
$V_{IL}$	Input LOW Voltage:		all inputs		0.8	V	$V_{CC} = 5.0\text{V}$
$V_{IH}$	Input HIGH Voltage:	2.0	all inputs			V	$V_{CC} = 5.0\text{V}$
$I_{CC}$	Power Supply Current(2)			90	130	mA	
$V_{OL}$	Output LOW Voltage:		all outputs	.3	.45	V	$I_{OL} = 10\text{ mA}$
$V_{OH}$	Output HIGH Voltage:	2.4	ENLG output	3.0		V	$I_{OH} = -1\text{ mA}$
$I_{OS}$	Short Circuit Output Current:	-15	ENLG output	-35	-55	mA	$V_{CC} = 5.0\text{V}$
$I_{CEX}$	Output Leakage Current:		IA and A <sub>0</sub> -A <sub>3</sub> outputs		100	$\mu\text{A}$	$V_{CEX} = 5.5\text{V}$

## NOTES:

(1) Typical values are for  $T_A = 25^\circ\text{C}$  and nominal supply voltage.

(2) B<sub>0</sub>-B<sub>2</sub>, SGS, CLK, R<sub>0</sub>-R<sub>4</sub> grounded, all other inputs and all outputs open.

## A.C. CHARACTERISTICS

 $T_A = -55^\circ\text{C to } +125^\circ\text{C}; V_{CC} = 5.0\text{V} \pm 10\%$ 

SYMBOL	PARAMETER	LIMITS			UNIT
		MIN	TYP <sup>(1)</sup>	MAX	
t <sub>CY</sub>	CLK Cycle Time <sup>(5)</sup>	85			ns
t <sub>PW</sub>	CLK, ECS, IA Pulse Width	25	15		ns
<i>Interrupt Flip-Flop Next State Determination:</i>					
t <sub>ISS</sub>	ISE Set-Up Time to CLK	16	12		ns
t <sub>ISH</sub>	ISE Hold Time After CLK	20	10		ns
t <sub>ETCS</sub> <sup>2</sup>	ETLG Set-Up Time to CLK	25	12		ns
t <sub>ETCH</sub> <sup>2</sup>	ETLG Hold Time After CLK	20	10		ns
t <sub>ECSS</sub> <sup>3</sup>	ECS Set-Up Time to CLK (to clear interrupt inhibit prior to CLK)	85	25		ns
t <sub>ECCH</sub> <sup>3</sup>	ECS Hold Time After CLK (to hold interrupt inhibit)	0			ns
t <sub>ECRS</sub> <sup>3</sup>	ECS Set-Up Time to CLK (to enable new requests through the request latch)	110	70		ns
t <sub>ECRH</sub> <sup>3</sup>	ECS Hold Time After CLK (to hold requests in request latch)	0			ns
t <sub>ECSS</sub> <sup>2</sup>	ECS Set-Up Time to CLK (to enable new status through the status latch)	85	70		ns
t <sub>ECSH</sub> <sup>2</sup>	ECS Hold Time After CLK (to hold status in status latch)	0			ns
t <sub>DCS</sub> <sup>2</sup>	SGS and B <sub>0</sub> -B <sub>2</sub> Set-Up Time to CLK (current status latch enabled)	90	50		ns
t <sub>DCH</sub> <sup>2</sup>	SGS and B <sub>0</sub> -B <sub>2</sub> Hold Time After CLK (current status latch enabled)	0			ns
t <sub>RCS</sub> <sup>3</sup>	R <sub>0</sub> -R <sub>7</sub> Set-Up Time to CLK (request latch enabled)	100	55		ns
t <sub>RCH</sub> <sup>3</sup>	R <sub>0</sub> -R <sub>7</sub> Hold Time After CLK (request latch enabled)	0			ns
t <sub>ICS</sub>	IA Set-Up Time to CLK (to set interrupt inhibit F.F. before CLK)	55	35		ns
t <sub>CI</sub>	CLK to IA Propagation Delay		15	30	ns
<i>Contents of Request Latch and Request Level Output Status Determination:</i>					
t <sub>RIS</sub> <sup>4</sup>	R <sub>0</sub> -R <sub>7</sub> Set-Up Time to IA	10	0		ns
t <sub>RIH</sub> <sup>4</sup>	R <sub>0</sub> -R <sub>7</sub> Hold Time After IA	35	20		ns
t <sub>RA</sub>	R <sub>0</sub> -R <sub>7</sub> to A <sub>0</sub> -A <sub>2</sub> Propagation Delay (request latch enabled)		80	100	ns
t <sub>ELA</sub>	ELR to A <sub>0</sub> -A <sub>2</sub> Propagation Delay		40	55	ns
t <sub>ECA</sub>	ECS to A <sub>0</sub> -A <sub>2</sub> Propagation Delay (to enable new requests through request latch)		100	130	ns
t <sub>ETA</sub>	ETLG to A <sub>0</sub> -A <sub>2</sub> Propagation Delay		35	70	ns

## A.C. CHARACTERISTICS (CON'T)

SYMBOL	PARAMETER	LIMITS			UNIT
		MIN	TYP <sup>(1)</sup>	MAX	
<i>Contents of Current Priority Status Latch Determination:</i>					
$t_{DECS}^4$	SGS and B <sub>0</sub> -B <sub>2</sub> Set-Up Time to ECS	20	10		ns
$t_{DECH}^4$	SGS and B <sub>0</sub> -B <sub>2</sub> Hold Time After ECS	20	10		ns
<i>Enable Next Level Group Determination:</i>					
$t_{REN}$	R <sub>0</sub> -R <sub>7</sub> to ENLG Propagation Delay		45	70	ns
$t_{ETEN}$	ETLG to ENLG Propagation Delay		20	30	ns
$t_{ECRN}$	ECS to ENLG Propagation Delay (enabling new request through the request latch)		85	110	ns
$t_{ECSN}$	ECS to ENLG Propagation Delay (enabling new SGS through status latch)		35	55	ns


## NOTES:

- (1) Typical values are for  $T_A = 25^\circ\text{C}$  and nominal supply voltage.  
 (2) Required for proper operation if ISE is enabled during next clock pulse.  
 (3) These times are not required for proper operation but for desired change in interrupt flip-flop.  
 (4) Required for new request or status to be properly loaded.  
 (5)  $t_{CY} = t_{ICS} + t_{CI}$

## TEST CONDITIONS:

Input pulse amplitude: 2.5 volts.  
 Input rise and fall times: 5 ns between 1 and 2 volts.  
 Output loading of 15 mA and 30 pf.  
 Speed measurements taken at the 1.5V levels.

## TEST LOAD CIRCUIT

CAPACITANCE<sup>(5)</sup>

$T_A = 25^\circ\text{C}$

SYMBOL	PARAMETER	LIMITS			UNIT
		MIN	TYP <sup>(1)</sup>	MAX	
$C_{IN}$	Input Capacitance		5	10	pf
$C_{OUT}$	Output Capacitance		7	12	pf

## TEST CONDITIONS:

$V_{BIAS} = 2.5\text{V}$ ,  $V_{CC} = 5\text{V}$ ,  $T_A = 25^\circ\text{C}$ ,  $f = 1\text{MHz}$

## NOTE:

- (5) This parameter is periodically sampled and not 100% tested.

WAVEFORMS

